



## PP200G Premium Grey Gasket (Pressure Pack)

Document version: May 13, 2024



### Description

This premium gasket sealant grey is an oxime neutral sealant with excellent resistant to oils, which is specially developed for crankcase covers, oil crankcases and proven at Porsche.

This replacing gasket of engine components is suitable for transmission covers, cylinder head covers, differentials and water pumps. With a temperature resistance of up to 250 °C and a perfect adhesion, also without primer, the gasket can be used on surfaces of aluminum, various metals, plasticizer-free plastics like polycarbonates, polyester, rigid polystyrene, ABS and most type of rigid PVC. The Pressure Pack enables to replace the gasket in an easy and simple way in the right proportions. After application the silicone cures with atmospheric moisture to form a durable rubber seal. MPM Premium Gasket Sealant is not paintable and not recommended for PE, Teflon, PP surfaces.

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
PP200G	0.2 L	6	-

### Standard analyses

TEST	VALUE	METHOD
Density	1.18	kg/l
Colour	gray	
Base	Oxim	
Application Temperature	5 – 40	°C
Skin formation duration at 23 °C / 55% RF	~ 5	min.
Temperature Resistance After Curing	-60 – 250	°C
Silicone Based		
Uv Colour And Weather Resistant		
Sensor Safe		

These characteristics are typical of current production. Variations in these characteristics may occur.