88000A Antifreeze MPG

Version du document: 21 avr. 2024

Description

Cet antigel sans silicate MPG (Mono Propylene Glycol) offre une excellente protection contre le gel aux alliages d'aluminium et de métal. Le produit écologique et inoffensif est notamment utilisé dans les bateaux et les camping-cars contre le gel des moteurs (embarqués), pour les systèmes d'eau potable et les toilettes. Son caractère écologique lui permet d'être dilué sans danger. Le MPG peut également être appliqué dans l'industrie alimentaire. Avant l'emploi, cet antigel doit encore être dilué dans la proportion d'eau recommandée.

Selon les spécifications de

VW TL 52 176

Unités d'emballage

ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
88005A	5 L	4	112
88020A	20 L	1	30
88060A	60 L	1	6
88205A	205 L	1	2
88999A	1000 L	1	-

Analyses standard

TEST	VALEUR		METHOD
Density à 20 °Celsius	1.042	kg/l	
Colour	fluorescent orange / red		
Freezing point at ⅓ antifreeze + ⅔ water	-16	°C	
Freezing point at 1 antifreeze + 1 water	-36	°C	
Boiling Point	165	°C	
Water	4	mass%	
Copper Corrosion Test-reserve Alkanity	6.3		

These characteristics are typical of current production. Variations in these characteristics may occur.

MPM International Oil Company B.V. Cyclotronweg 1 2629 HN Delft
Numéro de fax: +31 (0) 15/ 251.40.31 info@mpmoil.nl www.mpmoil.nl